

CLAIMS

1. A circuit comprising:

a register stack configured as (i) a plurality of segments addressable through a segment address signal and (ii) a plurality of registers within each of said plurality of segments, said plurality of registers being addressable through a register address signal; and

a control circuit configured to (i) store a plurality of register states, (ii) store a segment count signal, and (iii) present said segment address signal responsive to said plurality of register states, said segment count signal, and said register address signal.

2. The circuit according to claim 1, wherein at least one of said register states is fixed in a global state

3. The circuit according to claim 1, wherein at least one of said register states is fixed in a stackable state.

4. The circuit according to claim 1, wherein said register stack further comprises:

99-339
1496.00059

a first portion configured as at least one segment of said plurality of segments; and

5 a second portion remote from said first portion and configured as at least one segment of said plurality of segments.

5. The circuit according to claim 1, wherein said control circuit comprises:

a counter configured to present said segment count signal;

a status circuit configured to present a gating signal responsive to said register address signal; and

a plurality of logic gates configured to present said segment address signal responsive to said gating signal and said segment count signal.

6. The circuit according to claim 5, wherein said status circuit comprises:

a comparator configured to present said gating signal responsive to said plurality of register states and said register address signal.

09733485 121500
5 5848E260

99-339
1496.00059

7. The circuit according to claim 5, wherein said status circuit comprises:

a memory device configured to store said plurality of register states and present said gating signal responsive to said plurality of register states and said register address signal.

8. The circuit according to claim 5, wherein said plurality of logic gates are further configured to present said segment address as a predetermined address responsive to said gating signal having a global state.

9. The circuit according to claim 8, wherein said status circuit comprises:

a comparator configured to present said gating signal responsive to said plurality of register states and said register address signal.

10. A method of controlling a register stack comprising the steps of:

(A) comparing a register address with a plurality of register states to present a gating signal;

005738455 121500

99-339
1496.00059

5 (B) gating a segment count with said gating signal to present a segment address; and

(C) addressing said register stack with said register address and said segment address.

11. The method according to claim 10, wherein step (A) further comprises the sub-steps of:

presenting a signal communicating said plurality of register states; and

5 selecting one of said plurality of register states as said gating signal based upon said register address.

12. The method according to claim 10, further comprising the step of:

setting said plurality of register states in response to a reset handler operation.

13. The method according to claim 10, further comprising the step of:

incrementing said segment address in response to a push instruction.

09738485-121500
5,58485-121500

99-339
1496.00059

14. The method according to claim 13, further comprising
the step of:

decrementing said segment address in response to a pop
instruction.

09733455 121500
15. A circuit comprising:
means for storing a register stack configured as (i) a
plurality of segments addressable through a segment address and
(ii) a plurality of registers within each of said plurality of
segments, said plurality of registers being addressable through a
register address;

means for storing a plurality of register states;

means for storing a segment count; and

10 means for presenting said segment address responsive to
said register address and said plurality of register states and
said segment count.